

		HEAT LAMPS				STANDARD PRODUCTS							
		LINEAR DOUBLE-ENDED											
<p style="text-align: center;">Victory IR Lamps are the ideal high heat power source for a wide spread industrial heating applications such as paint and paper drying, food warming ,sterilization and many more.</p>													
General Industrial													
VOLTAGE	WATTS	LL	OAL	LIFE (HR)	DIA	CAP/BASE	B	R	VICTORY	Leads	Philips	Ushio	GE
230	300	60	119	5000	19	R7S	H		64243011				
230	300	60	119	5000	10	R7S	H		64243021		13908R		
240	500	130	227	5000	19	SK15	H		64245030				HH599
235	500	130	227	5000	19	SK15	H		64245010				HH210
235	500	130	227	5000	10	SK15	H		64245020		13169Z		HH188
120	500	130	241	5000	11	STRAP	H	Y	64125050		13169X/98	QIH240-500	
220-250	500	130	227.5	5000	11	SK15	H	Y	64245052		13169Z/98	QIH240-500ZD	
120	500	142	240	5000	10	STRAP	H		64125010		13169X		
235	700	150	213	5000	10	SK15	H		64247022		13842Z		
240	1000	280	370	5000	11	STRAP	H	Y	64241053		13195X/98	QIH240-1000ZS	
235	1000	280	357.5	5000	11	SK15	H	Y	64241052		13195Z/98	QIH240-1000ZD	
220-250	1000	280	370	5000	11	STRAP	U	Y	64241053		13713X/98	QIH240-1000VZS	
235	1000	280	357.5	5000	11	SK15	U	Y	64241052		13713Z/98	QIH240-1000VZD	
235	1000	241	369	5000	10	STRAP	H		64241027		13195X	QIH240-1000S	
220-250	1000	272	369	5000	10	STRAP	U		64241027		13713X	QIH240-1000VS	
144	1200	157	228	5000	11	Y-WIRES	H	Y	64141253		13561Y/98	QIH144-1200ZB	
144	1200	157	229	5000	11	SK15	H	Y	64141252		13561Z/98	QIH144-1200ZD	
144	1200	157	228	5000	11	SK15	H	Y	64231251		14134Z/98		
235	1200	155	227	5000	11	Y-WIRES	H		64141222		13561Y/00	QIH144-1200B	QH1200T3/CL
144	1600	157	229	5000	11	SK15	H	Y	64141653		13568Z/98		
144	1600	157	228	5000	11	SK15	H	Y	64141622		14135Z/98		
235	1600	155	227	5000	10	Y-WIRES	H		64231652		13568Y/00	QIH240-1600S	
220-250	2000	280	357.5	5000	11	SK15	U	Y	64242052		13168Z/98		
230	2000	580	658	5000	11	SK15	H	Y	64232022		13214Z/98		
400	2000	410	508	5000	11	STRAP	U	Y	64382051		13245X/98		
380-420	2000	410	508	5000	11	STRAP	U	Y	64382051		13765X/98		
230	2000	280	357.5	5000	11	SK15	H	Y	64402050		14103Z/98		
235	2000	700	787.5	5000	11	SK15		Y	64242058		14132Z/98		
235	2000	280	355	5000	11	SK15		Y	64242052		14136Z/98		
235	2000	286	349	5000	9	V-WIRES	U		64242028		13168V		
220-250	2000	282	369	5000	10	STRAP	U		64242021		13168X		
235	2000	410	507	5000	10	STRAP	H		64382021		13245X		
400	2500	280	355	5000	11	SK15		Y	64242550		14143Z/98		
400	3000	315	378	5000	10	SK15	H	Y	64403052		14111Z/98		
235	2500	315	378	5000	10	SK15	H		64402550		14106Z/98		
480	3000	280	355	5000	10	SK15	H	Y	64243055		14144Z/98		
380-420	3000	700	798	5000	11	STRAP	U	Y	64383052		13230X/98		
230	3000	700	787.5	5000	12	SK15	H	Y	64233050		14107Z/98		
380-420	3000	700	797	5000	10	STRAP	U		64383022		13215X		
235	3000	277	369	5000	13	STRAP	U		64403024		13565X		
480	3000	277	369	5000	13	STRAP	U		64243024		13565X		
480	3650	965	1057	5000	10	V-WIRES	H		64483620				3650T3/CL

480	3800	985	1062	5000	10	V-WIRES	H	64483820					3800T3/CL
570	3800	985	1062	5000	10	V-WIRES	H	64573820					
<b>ZONE HEATING</b>													
<b>Their instant' on' is delivering heat just where it is wanted . Flexibility, economy and energy efficiency, whenever and wherever needed.</b>													
235	1000	272	354	5000	10	SK15	H				15007Z		
235	1000	280	346	5000	19	SK15	H	64241030					HH450
240	1300	180	254	2000	12	R7S	H	64241372			15028R		
240	1500	280	346	5000	19	SK15	H	64241540	230mmfork		Neutral Density		
240	1500	280	354	5000	12	SK15	H	64241571			15004Z		
240	1500	280	346	5000	10	SK15	H	64241564	230mmfork		frosted/NDA		
240	1500	280	346	5000	19	R7s	H	64241565			Red satin/Plugin		
240	1500	280	346	5000	19	SK15	H	64241562	500mm push		Red satin/NDA		
240	1500	280	346	5000	19	SK15	H	64241530	230mmfork		HH451		
235	1500	280	354	5000	19	SK15	H	64121530			13123Z/876	QIH240-1500RD	HH451/QX8900
235	2000	280	354	5000	10	SK15	H	64242070			15005Z		
240	2000	280	354	5000	19	SK15	H	64242030			13934Z/876L	QIR240-2000RD	HH804
120	1500	280	354	5000	19	SK15	H	64121530			13123Z/876	QIH240-1500RD	HH451/QX8900
<b>PAINT DRYING</b>													
<b>Automotive paint drying responds to short wave Infra Red. Drying times are reduced, resulting in great energy savings.</b>													
100	850	119	197	5000	19	SK15	H	64118530			13833Z/876		
240	850	119	197	5000	19	SK15	H	64248531			13833Z/876		
240	1000	280	346	5000	11	SK15	U	6424103C					
235	1000	440	530	5000	19	SK15	U	64241034			13836Z/876		
235	1100	446	530	5000	19	SK15	U	64241036			13837Z/876		
240	1500	700	786	5000	19	SK15	U	6424153K			13846Z/876		
<b>NDA</b> (fast response medium)													
<b>Fast response medium wave is ideal for water based ink curing and many other applications</b>													
240	1000	272	355	5000	10	SK15	U	64231020	230mm fork				
220	1200	480	549	5000	10	SK15	H	64221223	240mm fork				
240	1500	438	511	5000	10	R7s	H	54241527M					
240	1500	508	562	5000	10	R7s	H	54241528					
240	1500	442	502	5000	10	R7s	H	5424152A					
220	1200	480	546	5000	10	SK15	H	64221223			low temp		
220	1200	480	546	5000	10	R7s	H	64221222					
235	1000	272	355	5000	10	SK15	H	64231024	250mmfork				
230	1000	390	450	5000	10	R7s	H	64231029					
230	1500	272	355	5000	10	SK15	H	64231523	300mmfork				
230	2000	650	715	5000	10	SK15	H	64232025	400mmfork				
240	1500	270	340	5000	10	R7s	H	64241501			frosted		
240	1500	425	494	5000	10	SK15	U	64241521	203mmcrimp				

240	1500	390	450	5000	10	R7s	H	64241527				
240	1500	556	613	5000	10	R7s	H	6424152B				
240	1500	620	689	5000	10	R7s	H	6424152E				
240	1500	430	494	5000	10	SK15	H	6424152L				
240	1800	508	562	5000	10	R7s	H	64241820				
240	2000	801	845	5000	10	R7s	H	6424202E				
415	1500	508	562	5000	10	R7s	H	6411521				
415	1500	457	511	5000	10	R7s	H	6411522				
415	1500	540	613	5000	10	R7s	H	64411526				
480	3800	980	1066	5000	10	SK15	H	64483820				
<b>HARD GLASS</b>		dia										
<b>Lamps are designed for profitable animal rearing. Resistant to thermal shock</b>												
240	375	R125		clear		E27		90243010				
240	300	R125		clear		E27		90243010				
240	250	R125		red		E27		90242512				
240	175	R125		clear		E27		90241710				
240	150	R125		clear		E27		90241511				
110	375	G30		clear		E27		90113710				
110	375	R125		clear		E27		90113712				
110	1000	G30		clear		E27		90111010				
<b>PAR 38</b>				pressed glass, energy saving								
240	150			clear								
240	150			red								
240	175			clear								
240	175			red								
<b>CERAMIC</b>												
<b>Long wave elements designed for thermoforming or where a uniform heating is required. No light just efficient heating with extra long life.</b>												
240	1000			FSC		full sized curved		FSC1000W240V				
230	250			FSC		full sized curved						
230	300			FSC		full sized curved						
230	350			FSC		full sized curved						
230	400			FSC		full sized curved						
230	500			FSC		full sized curved						
230	650			FSC		full sized curved						
230	750			FSC		full sized curved						
230	125			FSF		full sized flat						
230	150			FSF		full sized flat						
230	200			FSF		full sized flat						
230	250			FSF		full sized flat						
230	300			FSF		full sized flat						
230	350			FSF		full sized flat						
230	400			FSF		full sized flat						
230	500			FSF		full sized flat						
230	500			HSC		half sized curved						



								IRC300				
								IRZ1000				
								IRZ500				
								K504				
								K515F				
								Z9570				
						33X16		TTCSUPPORT1				
						23X11		TTCSUPPORT1				