



## Hard glass infrared lamps

Using special red doped borosilicate glass there is no need to use potentially hazardous lacquers.

### Product features

- 75% of the visible light is reduced with red filter
- Neck moulded to ensure caps will not come loose
- 5000 hour life

### Applications

- Catering
- Agricultural
- Paint drying
- Personal care



Hard glass clear



Hard glass red



PAR



G30 Round





# Technical Data

## Hard glass infrared lamps



### HLO25 heat lamp fitting

- Fitted with guard
- 2 power settings
- Max wattage 250W
- Complete with chain for suspending

## Range

Code	Volts (V)	Watts (W)	Cap	Bulb	Finish
<b>Hard glass clear</b>					
90241511	240	150	E27	R125	Clear
90241710	240	175	E27	R125	Clear
90112512	110	250	E27	R125	Clear
90242513	240	250	E27	R125	Clear
90243010	240	300	E27	R125	Clear
90113713	110	375	E27	R125	Clear
90243710	240	375	E27	R125	Clear
<b>Hard glass red</b>					
90241512	240	150	E27	R125	Red
90242512	240	250	E27	R125	Red
<b>PAR</b>					
PAR240175C	240	175	E27 PAR	PAR38	Clear
PAR240175R	240	175	E27 PAR	PAR38	Red
<b>G30 Round</b>					
90113710	110	375	E27 PAR	G30	Clear
<b>Heat lamp fitting</b>					
HLO25	-	-	-	-	-



# VICTORY

Victory Lighting (UK) Ltd

www.victorylighting.co.uk email: sales@victorylighting.co.uk  
tel. +44 (0)1727 815137

© Victory Lighting (UK) Ltd 2018  
The information contained in this literature is for general information purposes only. Victory Lighting (UK) Ltd endeavours to keep the information up to date and correct, but makes no representations or warranties of any kind, express or implied, about the completeness, accuracy, reliability, suitability or availability with respect to the information, products, services, or related graphics contained in this literature.

Victory Lighting (UK) Ltd accepts no liability for any loss or damage including without limitation, indirect or consequential loss or damage, or any loss or damage whatsoever arising from loss of data or profits arising out of, or in connection with, the use of this literature.

Distributed by