



## HEAT LAMPS STANDARD PRODUCTS

### LINEAR DOUBLE-ENDED

Victory IR lamps are the ideal high heat power source for a wide spread industrial heating applications such as paint and paper drying, food warming, sterilization and many more.

General Industrial													
VOLTAGE	WATTS	LL	OAL	LIFE (hr)	DIA	CAP/ BASE	B	R	VICTORY	LEADS	PHILIPS	USHIO	GE
230	300	60	119	5000	19	R7s	H		64243011				
230	300	60	119	5000	10	R7s	H		64243021		13908R		
240	500	130	227	5000	19	SK15	H		64245030				HH599
235	500	130	227	5000	19	SK15	H		64245010				HH210
235	500	130	227	5000	10	SK15	H		64245020		13169Z		HH188
120	500	130	241	5000	11	STRAP	H	Y	64125050		13169X/98	QIH240-500	
220-250	500	130	227.5	5000	11	SK15	H	Y	64245052		13169Z/98	QIH240-500ZD	
120	500	142	240	5000	10	STRAP	H		64125010		13169X		
235	700	150	213	5000	10	SK15	H		64247022		13842Z		
240	1000	280	370	5000	11	STRAP	H	Y	64241053		13195X/98	QIH240-1000ZS	
235	1000	280	357.5	5000	11	SK15	H	Y	64241052		13195Z/98	QIH240-1000ZD	
220-250	1000	280	370	5000	11	STRAP	U	Y	64241053		13713X/98	QIH240-1000VZS	
235	1000	280	357.5	5000	11	SK15	U	Y	64241052		13713Z/98	QIH240-1000VZD	
235	1000	241	369	5000	10	STRAP	H		64241027		13195X	QIH240-1000S	
220-250	1000	272	369	5000	10	STRAP	U		64241027		13713X	QIH240-1000VS	
144	1200	157	228	5000	11	Y-WIRES	H	Y	64141253		13561Y/98	QIH144-1200ZB	
144	1200	157	229	5000	11	SK15	H	Y	64141252		13561Z/98	QIH144-1200ZD	
144	1200	157	228	5000	11	SK15	H	Y	64231251		14134Z/98		
235	1200	155	227	5000	11	Y-WIRES	H		64141222		143561Y/00	QIH144-1200B	QH1200T3/CL
144	1600	157	229	5000	11	SK15	H	Y	64141653		13568Z/98		
144	1600	157	228	5000	11	SK15	H	Y	64141622		14135Z/98		
235	1600	155	227	5000	10	Y-WIRES	H		64231652		13568Y/00	QIH240-1600S	

# VICTORY

GENERAL INDUSTRIAL													
VOLTAGE	WATTS	LL	OAL	LIFE (hr)	DIA	CAP/BASE	B	R	VICTORY	LEADS	PHILIPS	USHIO	GE
220-250	2000	280	357.5	5000	11	SK15	U	Y	64242052		13168Z/98		
230	2000	580	658	5000	11	SK15	H	Y	64232022		13214Z/98		
400	2000	410	508	5000	11	STRAP	U	Y	64382051		13245X/98		
380-420	2000	410	508	5000	11	STRAP	U	Y	64382051		13765X/98		
230	2000	280	357.5	5000	11	SK15	H	Y	64402050		14103Z/98		
235	2000	700	787.5	5000	11	SK15		Y	64242058		14103Z/98		
235	2000	280	355	5000	11	SK15		Y	64242052		14136Z/98		
235	2000	286	349	5000	9	V-WIRES	U		64242028		13168V		
220-250	2000	282	369	5000	10	STRAP	U		64242021		13168X		
235	2000	410	507	5000	10	STRAP	H		64382021		13245X		
400	2500	280	355	5000	11	SK15		Y	64242550		14143Z/98		
400	3000	315	378	5000	10	SK15	H	Y	64403052		14111Z/98		
235	2500	315	378	5000	10	SK15	H		64402550		14106Z/98		
480	3000	280	355	5000	10	SK15	H	Y	64243055		14144Z/98		
380-420	3000	700	798	5000	11	STRAP	U	Y	64383052		13230X/98		
230	3000	700	787.5	5000	12	SK15	H	Y	64233050		14107Z/98		
380-420	3000	700	797	5000	10	STRAP	U		64383022		13215X		
235	3000	277	369	5000	13	STRAP	U		64403024		13565X		
480	3000	277	369	5000	13	STRAP	U		64243024		13565X		
480	3650	965	1057	5000	10	V-WIRES	H		64483620				3650T3/CL
480	3800	985	1062	5000	10	V-WIRES	H		64483820				3800T3/CL
570	3800	985	1062	5000	10	V-WIRES	H		64573820				

# VICTORY

## ZONE HEATING

Their instant 'on' is delivering heat where it is wanted. Flexibility, economy and energy efficiency, whenever and wherever needed.

VOLTAGE	WATTS	LL	OAL	LIFE (hr)	DIA	CAP/BASE	B	R	VICTORY	LEADS	PHILIPS	USHIO	GE
235	1000	272	354	5000	10	SK15	H				15007Z		
235	1000	280	346	5000	19	SK15	H		64241030				HH450
240	1300	180	254	5000	12	R7s	H		64241372		15028R		
240	1500	280	346	5000	19	SK15	H		64241540	230mm fork	Neutral Density		
240	1500	280	354	5000	12	SK15	H		64241571		15004Z		
240	1500	280	346	5000	10	SK15	H		64241564	230mm fork	Frosted/NDA		
240	1500	280	346	5000	19	R7s	H		64241565		Red satin/Plugin		
240	1500	280	346	5000	19	SK15	H		64241562	500mm push	HH451		
235	1500	280	346	5000	19	SK15	H		64121530		13123Z/876	QIH240-1500RD	HH451/QX8900
235	2000	280	354	5000	10	SK15	H		64242070		15005Z		
240	2000	280	354	5000	19	SK15	H		64242030		13934Z/876L	QIR240-2000RD	HH804
120	1500	280	354	5000	19	SK15	H		64121530		13121Z/876	QIH240-1500RD	HH451/QX8900

## PAINT DRYING

Automotive paint drying responds to short wave infrared. Drying times are reduced, resulting in great energy savings.

VOLTAGE	WATTS	LL	OAL	LIFE (hr)	DIA	CAP/BASE	B	R	VICTORY	LEADS	PHILIPS	USHIO	GE
100	850	119	197	5000	19	SK15	H		64118530		13833Z/876		
240	850	119	197	5000	19	SK15	H		64248531		13833Z/876		
240	1000	280	346	5000	11	SK15	U		6424103C				
235	1000	440	530	5000	19	SK15	U		64241034		13836Z/876		
235	1100	446	530	5000	19	SK15	U		64241036		13837Z/876		
240	1500	700	786	5000	19	SK15	U		6424153K		13846Z/876		